

CITTÀ



DI LODI

COMUNE di LODI

Direzione Organizzativa 3 - Piazzale Forni, 1 26900 Lodi

**RIQUALIFICAZIONE FUNZIONALE E MESSA IN SICUREZZA
DELLA SCUOLA PRIMARIA "DE AMICIS" NEL COMUNE DI
LODI**

(via della Calca 60, Lodi)

**Progetto di Fattibilità Tecnico Economica
Strutturale**

RIF. TAVOLA

COMMESSA

2 5 0 2

LIVELLO

P F T E

AMBITO

S

DOC

4 S

REV

0 1

ELABORATO

43

**ELABORATO GRAFICO
RINFORZO SOLAIO ZONA PRIMO AMPLIAMENTO**

Technical drawing of a reinforced concrete slab (Pavimento de concreto armado) showing a grid of beams and columns. The drawing includes dimensions for column spacing (e.g., 3675 mm, 3645 mm), beam dimensions (e.g., 200 mm x 300 mm), and reinforcement details (e.g., Aço 200, Aço 220). The slab is labeled "Pavimento de concreto armado" and "Pavimento 1". The drawing is divided into sections labeled "PARTICULAR 1" through "PARTICULAR 9".

[illegible]

The image contains two architectural drawings of a concrete floor slab, labeled 'PIANTA' and 'SEZIONE A'.

PIANTA (Plan View): This drawing shows the top-down view of the floor slab. It is a rectangular slab with a width of 200 units and a depth of 80 units. The slab is supported by a wall on the left side, indicated by a dashed line. The wall has a height of 200 units. The slab is labeled 'PAV. 220' and 'MUR. 220'. The wall is labeled 'MUR. 220' and 'MUR. 220'. The slab is labeled 'PAV. 220' and 'MUR. 220'.

SEZIONE A (Section A): This drawing shows a cross-section of the floor slab. The slab has a thickness of 80 units. It is supported by a wall on the left side, which has a height of 200 units. The wall is labeled 'MUR. 220' and 'MUR. 220'. The slab is labeled 'PAV. 220' and 'MUR. 220'. The wall is labeled 'MUR. 220' and 'MUR. 220'. The slab is labeled 'PAV. 220' and 'MUR. 220'.

[illegible]

Technical drawing showing a cross-section (SEZIONE) and elevation (PROSPETTO) of a wall and slab connection. The wall is made of brickwork (MUR) and the slab is concrete (PIASTRA). The drawing includes dimensions for the wall thickness (220 mm), the slab thickness (80 mm), and the height of the wall above the slab (1500 mm). It also shows the reinforcement details, including the use of HEA 220 bars and the placement of the slab reinforcement (AS 200/200 mm). The drawing is labeled "SEZIONE IN CORRISPONDENZA PIASTRA" and "PROSPETTO".

[illegible][illegible]

COLEGAMENTO
MURO

SEZIONE

MURO ESISTENTE
1500x200 mm
L=200 mm

MURO A TESSA
200x200 mm
L=200 mm

SOLIDO ESISTENTE
200x200 mm
L=200 mm

PIANTA

MURO ESISTENTE
200x200 mm
L=200 mm

MURO A TESSA
200x200 mm
L=200 mm

COLEGAMENTO
MURO

COLLEGAMENTO ANGOLARE 150x60x10 AL MURO ESISTENTE

PROSPETTO

SEZIONE

[illegible]

NOTA PER SALDATURE

– LE SALDATURE A CORDONE D'ANGOLO SI INTENDONO CONFORMI ALLA UNI 10011 CON IL SEGUENTE SCHEMA:



$SP = 0,7 \times S$
 $S =$ SPESSORE LAMIERA PIU' SOTTILE

PIANTA CHIAVE		SECONDO AMPLIAMENTO 1972-1973 (non oggetto di questo intervento)	EDIFICIO ORIGINARIO PRIMO '900
			PRIMO AMPLIAMENTO 1958-1959